

PROTUFF

SURFACE TOLERANT EPOXY

Where there is salt and moisture, there is corrosion. Corrosion causes safety issues and loss of assets. **Stop it effectively and economically.**

If you have this at your plant...



You don't have a lot of...



And damp surfaces are a problem...



PROTUFF

SURFACE TOLERANT EPOXY

PROTUFF 2225 ALUMINUM MASTIC EPOXY
PROTUFF 2215 EPOXY MASTIC PRIMER
PROTUFF 3300 EPOXY MASTIC COLORS

And your steel looks like this...



PROTUFF Series of epoxy coatings allows you to save time in surface preparation by avoiding the expense and hazard of abrasive blasting. Apply directly to high-pressure washed surfaces and recoat or place steel back in service within hours, not days.

PROTUFF Epoxy Mastics are formulated and tested to allow application over damp surfaces and in dew point conditions. Coat directly after washing or even below the dew point number, keeping production on schedule keeps dollars from being spent.

PROTUFF Materials are also low-temperature cure, allowing for Fall and Winter applications when plant demands or lessened and contractor rates are lower.

- Apply over corroded steel
- Apply over damp substrates
- Brush, roll or spray
- Apply at temperatures as low as 20F/-6C
- Superior bonding
- PROTUFF 2225 can even be applied over 50-ppm of chloride contamination

THEN YOU NEED PROTUFF!



To access product data sheets or schedule a review and estimate for coating your steel scan the QR or go directly to our web site.



072516